


SA / RK - Vanne de purge manuelle, semi-automatique ou automatique, pour systèmes de traitement d'air, en laiton, plastique ou inox

Manual drain	The manual drain can be opened by screwing it into the bowl. Once the collected condensate reaches the drain hole, it is being relieved.
Semiautomatic drain	The semiautomatic drain semiautomatically separates condensates from compressed air or gas systems. After operating pressure switch-off the drain valve opens and the collected condensate is being relieved.
Automatic drain	The automatic drain fully automatically separates condensates from compressed air or gas systems. Once the float lifts from the valve seat caused by the condensate level, the condensate is being relieved. Operating pressure must be 2 bar minimum.
Temperature range	0 °C to 50 °C / 32 °F to 122 °F 0 °C to 80 °C / 32 °F to 176 °F for manual drain made of brass for appropriately conditioned compressed air down to -30 °C / -22 °F



Drain valves

Valve type	Description	For filter / filter regulator	For bowl type	Operating pressure max. bar	Order number
------------	-------------	-------------------------------	---------------	-----------------------------	--------------

Drain valves		1/8" - 27 NPSM thread of internal valve			SA/RK
manual drain	made of brass	F20 / F504 / F602 / B11 / B12 / B20 / B21 / B548	all	21	SA600Y-71
	made of plastic	F20 / F504 / F602 / B11 / B12 / B20 / B21 / B548	all	21	AWF-10
semiautomatic drain drainage after pressure switch-off	piston drain	F504	all	12	RK504SY
		F602-02/-03	A/B/W	12	RK602SY
	spring-loaded	B11 / B12	all	12	4210
		F20	all	12	4212
		F20 / F504 / F602 / B11 / B12 / B20 / B21 / B548	all	12	RK504SY RK500SY
automatic drain	internal mounting effective from 2 bar on	F20 / F602 / B11 / B12 / B20 / B21 /	all	12	SA605MD
		F20 / F602 / B20 / B21	all	16	SA702MD
	external mounting	F602-04 to -20	A/B/W	18	SA602D
		F602-04 to -20	E/F	18	SA603D



SA600Y-71 AWF10
manual drains



RK504SY PKF35
piston drains



RK500SY
semiautomatic drain



SA605MD SAF105MD
internal automatic drains

Drain valves made of SST		1/8" - 27 NPSM valve thread			SA
automatic drain	internal mounting effective from 2 bar on	F10 / F11 / B11-S	all	12	SA10MDSS



SA602D
external automatic drain



SA603D
external automatic drain